

Material/Finish
 SPE-HB
 Main Body
 PEEK (Polyether Ether Ketone) (Light Brown)

*1: This is the value for the resin material. The operating temperature of the product changes with performance conditions such as tightening torque.

Heat Resistance Temperature* 1 260℃

- PEEK is a thermoplastic super engineering plastic superior in physical and chemical properties.
- Excellent chemical resistance. It remains almost unaffected by chemicals other than concentrated sulfuric acid, concentrated nitric acid, and concentrated hydrofluoric acid.
- With excellent heat resistance and water resistance, it retains strength at high temperatures.
- It features outstanding resistance to wear, shock, and fatigue.
- It also has high flame retardance which clears the UL 94 V-0 standard.
- The properties and precautions of plastic screws
 → P.xxxx

Unit:mm

Part Number	M (Coarse)			- L √12										В	Mass (g)	Qty
	Nominal of Thread 📶	Pitch												Ь	Mass (g)	per Pack
SPE-M3-HB	M3	0.5	4	5	6	8	10	12						6	0.14 - 0.41	5
SPE-M4-HB	M4	0.7		5	6	8	10	12	15					7	0.22 - 0.66	5
SPE-M5-HB	M5	0.8			6	8	10	12	15	18	20			8	0.32 - 1.1	5
SPE-M6-HB	M6	1							15	18	20			10	1.2 - 1.6	5
SPE-M8-HB	M8	1.25									20	25	30	13	2.6 - 3.9	5

• When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

• Part number specification

