


SVSLG Vented Socket Head Cap Screws - High Intensity Stainless Steel



Vacuum
 Cleanroom wash & packaging
 Heat-resistance
 Chemical-proof
 Non-Magnetic
 High strength
 SUS Stainless steel



● Application

Vacuum devices / Vacuum chambers / FPD production equipment / Semiconductor devices / Electron microscopes

● Material/Finish



	SVSLG
Main Body	SUS316L

● Mechanical property

	SUS316L*1
Tensile Strength (N/mm ²)	1000
0.2% Proof Load (N/mm ²)	800
Elongation(mm)	0.3d

*1 : In-house specification value. Confirmed with test pieces from each **SVSLG** production lot.

● For other mechanical properties refer to **SVSLG**. ➔ P.xxxx

- The ventilation hole easily releases gas trapped in the screw holes of equipment and machines, and supports vacuum drawing of vacuum devices.
- Hex socket head cap screw with ventilation hole - high intensity stainless steel **SVSLG** (➔ P.xxxx).
- Tensile strength 1000 N/mm², 0.2% proof load 800 N/mm²
- The proof load is approximately 1.8 times that of general stainless steel hex socket head cap screws. Therefore, smaller screw diameters and reduced quantities are available to save space and reduce weight.
- Made of SUS316L. It has excellent corrosion resistance.
- Non-magnetic.
- Cleanroom wash/cleanroom packing provided. ➔ P.xxxx


Unit : mm

Part Number	M (Coarse)		L								D1	L1	B	d	Mass (g)	Qty per Pack
	Nominal of Thread	Pitch	6	8	10	12	15	20	25	30						
SVSLG-M3	M3	0.5									5.5	3	2.5	1.2	0.64 - 1.45	10
SVSLG-M4	M4	0.7		8	10	12	15	20	25		7	4	3	1.5	1.4 - 2.7	10
SVSLG-M5	M5	0.8			10	12	15	20	25	30	8.5	5	4	1.5	2.5 - 5.1	10
SVSLG-M6	M6	1				12	15	20	25	30	10	6	5	2	4.7 - 7.3	10

● When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

● Usage example

Gas trapped at the bottom of a screw hole is released through **SVSLG**, and gas trapped in a drilled hole is released through **SWAS-VF** (➔ P.xxxx).



● Related Products

For ventilation of drilled hole, please use **SWAS-VF**.



● Part number specification

SVSLG-M4-12

Product Code

Individual Sales ➔ P.xxxx	Cleanroom Wash & Packaging ➔ P.xxxx	Screw Length Adjustment ➔ P.xxxx	Vibration Resistant ➔ P.xxxx	Modification process for captive use ➔ P.xxxx
Available / Add'l charge	Cleanroom washed and packed	Available / Add'l charge	Not Available	Please feel free to contact us